

Estrades Drill Hole Results

Hole #	From (m)	To (m)	Intercept (m)	TW (m)	Au Eq** (g/t)	Zn Eq** (g/t)	Au (g/t)	Ag (g/t)	Zn (%)	Cu (%)	Pb (%)	Type** *	Azimuth	Dip	UTM		Total Depth (m)
															Northing	Easting	
															GWM-17E-01	106.80 112.90	
GWM-17E-02	263.25 274.35 329.60 339.90	264.25 275.35 334.50 341.15	1.00 1.00 4.90 1.30	0.60 0.60			0.6 0.9		0.9		0.8	DSS DSS DSS DSS	340°	-65°	5494924	655858	348
GWM-17E-03	372.85 374.50 384.10 386.05 389.70 395.70	373.60 375.50 385.00 387.00 391.15 396.70	0.75 1.00 0.90 0.95 1.45 1.00						0.5 1.4		0.4 0.7 0.7 0.6	DSS DSS DSS DSS DSS DSS	314°	-67	5494924	655858	454
GWM-17E-04	303.40 including 303.70	305.00 304.30	1.70 0.60	1.20 0.04			0.6 1.3	62.0 159.0	0.5	5.1 12.9		MSS MSS	3°	-55°	5494801	655626	368
GWM-17E-05	355.00	356.90	1.90	1.20			1.4	89.9	0.3	7.4	0.7	MSS	354°	-67°	5494801	655626	456
GWM-17E-06	341.80 including 343.30	344.40 343.80	2.70 0.50	1.70 0.30	29.2		2.8 7.8	111.3 162.6	4.0 1.0	4.7 11.2	0.2	MSS MSS	343	-64°	5494801	655626	432
GWM-17E-07	611.20 615.50	611.90 618.00	0.80 2.50	0.50 1.70							*0.9	DSS DSS	343°	-69°	5494701	655646	705
GWM-17E-08	804.60 including 804.60 including 811.25	822.25 806.65 815.80	17.70 2.00 4.50			10.8 15.2 22.3	1.1 1.0 1.7	95.2 147.6 190.9	4.2 8.3 9.7	0.6 0.2 1.3	0.3 0.6 0.5	MSS MSS MSS	204°	-49	5495170	654348	945
GWM-17E-08W5	646.50 650.00	647.50 651.00	1.00 1.00			8.1 1.1			8.1 1.1			SMS SMS	207.7°	-64.3	5495170	654348	354
GWM-17E-09	121.10 including 121.60	123.80 122.10	2.70 0.50	1.80 0.30		9.6 18.2	0.4 0.9	121.0 166.7	2.7 7.8	0.9 1.4	0.2	MSS MSS	26°	-55°	5494885	655354	192
GWM-17E-10	69.50 77.10	70.35 77.85	0.85 0.75	0.70 0.60					1.2 0.6		1.0	SMS SMS	77	-50	5494900	655300	150
GWM-17E-11	No significant values												308°	-56°	5494885	655354	222
GWM-17E-12	215.20 232.00 238.15 247.65	218.10 233.10 238.75 248.65	2.70 1.10 0.60 1.00	1.70 0.70 0.40 0.60		4.7	0.4	68.2	2.1 0.8 2.5 0.6		0.5 0.6	SMS DSS DSS DSS	13°	-58	5494833	655365	270
GWM-17E-13	124.30 including 125.80	126.60 126.60	2.40 0.90	1.00 0.40		9.2 18.4	0.8 1.9	54.7 92.4	4.9 10.9	0.3 0.5	0.5 1.6	MSS MSS	357° 13°	-73° -58	5494834 5494833	655151 655365	160 270
GWM-17E-14	259.30 including 259.30	262.00 260.70	2.70 1.40	1.40 0.70		16.4 21.7	1.5 2.5	121.0 137.4	6.0 10.4	1.3 0.7	0.8 1.4	MSS MSS	351°	-69°	5494746	655180	321
GWM-17E-15	200.80 including 203.35	204.40 204.40	3.60 1.10	2.50 0.70	5.5 15.9	10.2 29.2	2.0 6.5	45.9 123.6	3.6 9.6	0.4 1.0	0.5 1.5	SMS SMS	11°	-52	5494746	655180	252

GWM-17E-16	279.00	280.55	1.60	0.80	31.9			22.4	199.3	10.4		2.0	MSS	17°	-69	5494746	655180	420
	275.00	276.00	1.00	0.50	5.2	9.6	2.1	85.9	2.9		0.6	DSS						
	298.10	300.10	2.00	1.00						1.2		DSS						
	301.60	302.40	0.80	0.40				17.0	2.6	0.4		DSS						
	304.20	305.30	1.10	0.55		2.2	0.3		1.6			DSS						
	315.30	316.15	0.85	0.43			0.3	36.0	1.4	2.2		SMS						
	316.60	317.20	0.60	0.30			0.2	12.6		0.7		SMS						
	354.95	355.50	0.55	0.28					0.9			DSS						
GWM-17E-19	Stopped due to deviation. Will be continued later.													341°	-69	5494557	655421	219
GWM-17E-19A	No significant values													335°	-72	5494557	655421	852
GWM-17E-19AW1 including	707.15	709.00	1.90	1.40	6.6	12.2	1.8	70.9	6.1	0.3			MSS	337°	-62	5494557	655421	505
	707.15	707.70	0.50	0.40	13.0	23.9	5.0	88.1	10.5	0.4	0.7	MSS						
	711.00	713.00	2.00	1.60				15.0		0.6		SMS						
	719.50	720.50	1.00	0.80						0.5		DSS						
	824.40	724.90	0.50	0.40						0.5		DSS						
GWM-17E-24	71.65	73.70	2.10	1.20		21.3	2.3	65.7	12.6	0.8	0.3	MSS	149°	-59	5494966	654430	306	
	411.40	412.85	1.50	0.80	17.9	32.9	5.2	198.7	15.7	0.4	1.3	MSS						
GWM-17E-25 including	57.00	64.35	7.40	5.00								1.4	DSS	169°	-51	5494966	654430	467
	63.35	64.35	1.00	0.70	6.8			2.6		2.8	1.6	MSS						
	79.60	80.10	0.50	0.34	1.5	2.8	1.0		1.0			MSS						
GWM-17E-26 including	73.00	74.50	1.50	0.85	3.7		1.4	44.4		1.0				169°	-61	5494966	654430	600
	74.00	74.50	0.50	0.30				3.2	27.7									
	91.80	94.80	3.00	2.03		9.9	0.8	38.3	2.5	1.6								
GWM-17E-27 including including	82.60	84.40	1.80	1.10	12.3			4.7	67.5	4.9	2.1	1.0	MSS	146°	-63	5494966	654430	522
	59.00	60.00	1.00	0.65							2.0		DSS					
	79.75	80.75	1.00	0.65					24.6		1.3		DSS					
	103.00	105.00	2.00	1.30				0.3	15.7		0.6		DSS					
	285.55	286.40	0.85	0.55	1.7			1.2	36.8				MSS					
	295.60	298.30	2.60	1.69	6.3			5.7	43.2				MSS					
	499.75	503.08	3.30	2.15		39.1	2.2	181.0	28.5	0.3	0.9	MSS						
	502.00	503.08	1.10	0.72		50.5	4.8	145.5	36.6	0.2	0.7	MSS						
	521.25	523.90	2.60	1.69		26.2	0.3	190.7	18.6	0.5	0.5	MSS						
	521.25	523.00	1.80	1.10		34.0	0.4	222.8	25.0	0.6	0.6	MSS						
GWM-18E-17 including	299.80	301.00	1.20	0.70	4.5	8.3	1.5	30	2.9	0.6			SMS	336.9°	-72.4	5494746	655180.14	378
	302.00	303.00	1.00	0.60				56.1	0.4	2.2			SMS					
	307.90	309.40	1.60	0.90				0.2	76.1	0.4	3.7		MSS					
	307.90	308.40	0.50	0.30				0.4	175.8	0.8	9.4		SMS					
GWM-18E-18 including and and and	424.50	426.30	1.80	0.90				1.0	11.9		2.2		DSS	316	-78	5494732	655146	453
	425.70	426.30	0.60	0.30				2.2	18.5		4.7		DSS					
	381.80	382.50	0.60	0.30		4.1	0.3	27.5	1.9	0.2		DSS						
	388.90	390.40	1.50	0.70				0.4	25.5		1.0	SMS						
	420.40	421.20	0.80	0.40				0.5	64.8		3.6		DSS					
GWM-18E-28C including	101.00	103.30	2.30	1.20	20.1	36.9	10.6	60.4	10.1	1.3	2.0	MSS	135.6°	-69.5	5494965	654429	823	
	102.70	103.30	0.60	0.30	32.0		23.9	79.4	9.4	0.3	2.9	MSS						
	134.00	135.20	1.20	0.60	9.4		3.6	41.5	0.5	3.0		SMS						

GWM-18E-29	391.00	393.00	2.00	1.00		4.6	0.6	37.3	1.3	0.4	SMS	1	-79	5494732	655146	486	
including	391.00	392.00	1.00	0.50			1.2	58.5	1.4	0.7	SMS						
and	404.00	404.50	0.50	0.20			0.4	23.6		1.6	SMS						
and	440.40	441.20	0.80	0.40				7.7		2.3	SMS						
and	445.70	446.30	0.60	0.30						1.3	SMS						
and	447.30	448.10	0.90	0.40						1.2	SMS						
and	459.00	460.00	1.00	0.50		5.5		10.2	3.4	0.6	SMS						
and	475.00	478.00	3.00	1.50				4.9	0.1	0.5	SMS						
including	475.00	475.80	0.80	0.40				19.6		1.1	SMS						
including	477.50	478.00	0.50	0.20		2.5				0.7	SMS						
GWM-18E-30A	453.70	456.90	3.20	2.30	4.1	7.6	2.5	23.5	2.4		MSS	321.6°	-64.5	5494596	654847.72	480	
GWM-18E-31	496.70	503.10	6.40	4.40	9.0		6.9	78.5	1.7		SMS	334.9°	-71.1	5494596	654847.72	522	
including	496.70	498.30	1.60	1.10	26.6		21.9	113.1	5.6		MSS						
which includes	496.70	497.60	0.90	0.60	39.8		33.1	152.5	8.3		MSS						
including	501.00	503.10	2.10	1.40	7.0		4.3	154.8	0.9		MSS						
which includes	501.60	502.30	0.80	0.50	8.3		8.3				MSS						
GWM-18E-32	490.30	495.70	5.40	3.40		29.8	3.0	176.0	17.9	0.3	0.9	MSS	175	-66	5494933	654553	150
GWM-18E-41	531.40	532.10	0.70	0.40	5.0	9.2	1.9	13.9	5.3			SMS	326	-77	5494618	654950	552
and	533.10	533.70	0.70	0.40			0.5	21.9		0.9		SMS					
GWM-18E-42	361.80	366.60	4.80	3.30		14.8	1.3	88.1	6.5	0.7	0.3	MSS	334	-67	5494618	654950	450
including	361.80	363.80	2.00	1.40		23.7	1.7	95.0	14.5	0.5	0.8	MSS					
and	352.90	354.00	1.10	0.80	2.6		1.3	33.9	1.1		0.4	MSS					
and	359.20	359.70	0.50	0.30				36.4		1.3		SMS					
and	371.40	372.40	1.00	0.70			0.6	74.5	3.0	4.1		SMS					
GWM-18E-43	331.70	338.50	6.80	5.10	4.2	7.7	1.5	40.0	3.9			MSS	359	-66	5494618	654950	444
including	331.70	336.40	4.70	3.50	4.9	9	1.8	35.3	4.8			MSS					
GWM-18E-45	503.80	506.00	2.20	1.50	2.8	5.1	1.3	20.6	2.2			MSS	327	-70	5494583	654821	522
GWM-18E-46B	473.10	475.00	1.90	0.90				15.8		2.2		DSS	22.9	-80.2	5494732	655146	522
including	474.40	475.00	0.60	0.30						4.4		SMS					
and	388.30	388.80	0.50	0.20						0.7		DSS					
and	436.60	437.20	0.60	0.30	2.5	4.7	0.9	26.4	2.3			DSS					
and	442.40	442.90	0.50	0.20		8.7	0.8	63.2	3.5	0.5	0.6	SMS					
and	451.70	452.40	0.80	0.40			0.3	37.9	0.3	2.9		DSS					
and	464.40	465.00	0.60	0.30			0.3			0.9		DSS					
and	466.40	466.90	0.50	0.20				22.3		1.9		DSS					
GWM-18E-47	405.90	414.30	8.40	5.10		5.1	0.2	25.9	2.4	0.5	0.1	DSS	15	-70	5494618	654950	501
including	405.90	407.80	1.90	1.20		8.2	0.4	42.7	4.3	0.6	0.2	DSS					
which includes	407.30	407.80	0.50	0.30		14.7	1.0	62.8	6.9	1.2	0.7	DSS					
including	411.00	411.80	0.80	0.50			0.6	31.6	3.5	3.6		SMS					
and	400.50	401.00	0.50	0.30		5.1		88.5	2.7			DSS					
and	416.50	417.50	1.00	0.60				15.9	0.5	1.9		DSS					
and	420.00	421.00	1.00	0.60		4.0		10.5	2.2	0.5		DSS					
including	345.00	347.90	2.90	2.10	19.7	36.3	6.0	212.5	16.2	0.6	1.8	MSS					
GWM-19E-49	104.40	106.25	1.85	0.90			1.6	130.8	4.6	5.7		MSS	351.5	-63	5494924	655582	120
including	105.50	106.25	0.75	0.40			1.7	169.3	4.7	7.8		MSS					

GWM-19E-50	132.75	137.45	4.70	1.90		22.2	1.8	81.8	10.3	2	0.4	DSS	351.5	-70	5494924	655582	174
including	132.75	133.50	0.75	0.30			0.6	93.4	0.7	3.2		DSS					
including	136.90	137.45	0.55	0.20			5	167.1	1.3	5.3		DSS					
GWM-19E-56	154.75	160.40	5.65	1.30	19.8	36.4	5.2	176.2	19.6	0.3	1.9	MSS	186	-62	5494904	654882.5	67
GWM-21E-33	47.00	47.65	0.65	0.50					0.6				322.5	-45	54949977	655887	102
	47.65	48.40	0.75	0.60			0.1	42.8	0.5	3.8							
	49.40	50.00	0.60	0.50					0.8								
	51.00	52.00	1.00	0.80				24.3		0.9							
GWM-21E-34	106.10	106.60	0.50				0.5	13.2		1.2			2	-48.5	5494990	655869	141
GWM-21E-35	123.50	124.50	1.00	0.70				0.6					351	-63.5	5494990	655869	201
GWM-21E-36	172.65	181.05	8.40	5.30	0.7			0.3	7.4	0.2			358	-68.5	5494990	655869	240
GWM-21E-38A	490.40	492.75	2.35	1.70		22	1.2	153	14.8	0.2	1.1	MSS	169	-69	5494933	654553	495
GWM-21E-39	694.00	694.55	0.55		1.2			0.4	9	0.4			170	-73	5494933	654560	702
GWM-21E-55	387.40	388.35	0.95	0.70				0.5	0.4				330	-65	5494646	655433	609
	558.55	560.30	1.75	1.30		8.9	0.9	73.5	3.8	0.5		MSS					
	566.40	566.90	0.50	0.40				0.6	68	0.7	2.6	SMS					
	574.00	574.75	0.75	0.60				0.2	25		1	DSS					
	579.80	580.40	0.60	0.50				0.2	4.5		0.8						
	162.80	168.00	5.20	1.20	11.6			8.5	57	4.2		MSS					
GWM-21E-57	274.10	276.80	2.70	2.10	35.1	64.5	10.7	423	22.8	2.8	2.6	MSS	184.5	-54.9	5494933	654553	297
GWM21E-59AW1	706.90	710.65	3.75	2.00				0.6	3.2		1.9	DSS	280	-80	5494894	655761	438
including	710.15	710.65	0.50	0.30				0.5	23.7		5.2	DSS					
	712.70	714.55	1.85	1.00				0.2			1.4	DSS					
	728.85	732.15	3.30	1.70						1.6							
GWM21E-60	557.75	558.25	0.50					0.1	5		1.4	DSS	286	-75	5494893	655773	678
	559.80	568.85	9.05	4.40	4.1			1.2	11.9	1	1.3	DSS					
including	564.60	568.85	4.25	2.00	5.2			1.6	17.8	0.9	1.7	DSS					
including	559.80	561.35	1.55	0.70	7.2			1.2	20.4	2.9	2.5	DSS					
including	560.85	561.35	0.50	0.20				0.7	35.5	1.7	4	DSS					
	566.30	566.80	0.50	0.20				12	14.6		3.6						
including	568.15	568.85	0.70	0.30				0.9	51.8	1.2	4.9	DSS					
	568.85	572.25	3.40	1.60						1.2		DSS					
	593.55	597.25	3.70	1.80							0.6						
GWM-21E-62	758.90	759.75	0.85					0.1			0.5		302	-73	5494542	655404	825
	763.30	764.30	1.00								0.6						
	767.85	768.45	0.60								0.7						
	769.80	770.35	0.55								0.6						
GWM-21E-64A	1051.50	1075.50	24.00	16.10								MSS	313	-79	5494542	655404	1248
including	1054.75	1056.15	1.40	0.90		8.5	0.7	14.2	6.8			MSS					
including	1054.75	1055.45	0.70	0.50		13.4	0.9	13.5	11.4			MSS					
including	1060.20	1060.75	0.55	0.40		2.9	0.5	7.7	1.8			MSS					
including	1064.50	1065.05	0.55	0.40		4.4		13.9	4			MSS					
including	1071.00	1074.00	3.00	2.00						0.9		MSS					
including	1051.50	1060.75	9.25	6.20		2.1	0.4	7.4	1.2			MSS					
	1084.55	1085.20	0.65				0.2	37.3		1.1							

GWM-21E-78	159.30	159.80					4.3	1.3	DSS	280	-80	5494894	655761	438
	166.00	167.00	1.00	0.80	9	0.3	7.7	4	1.4	DSS				
	170.70	176.00	5.30	4.00		0.4	9.5	0.3	1.4	DSS				
including	171.70	172.50	0.80	0.60		0.5	25.8	0.8	5.2	DSS				
	181.00	183.00	2.00	1.50	11.9	0.8	44.1	7.4	0.6	MSS				
GWM-21E-86	311.70	314.30	2.60	1.20		0.2	18.6		1.2		170	-73	5494903	654770
	343.00	343.75	0.75	0.30		0.2			1.5					
	392.80	395.80	3.00	1.30	16.1	13.9	50.7	1.1	0.5	MSS				
including	393.30	393.80	0.50	0.20	45.5	43.1	87.5	0.55		MSS				
	395.80	397.30	1.50	0.70		0.7	16.7	0.2	0.3					
	408.50	419.90	10.90	4.90		1.3	6.1	0.8						
	419.40	422.35	2.95	1.30	24	22.3	46.2	1.3	0.2	MSS				
PENDING	422.35	465.00												
PENDING	443.40	444.40	1.00							MSS				

Newiska Drill Hole Results

Hole #	From (m)	To (m)	Intercept (m)	TW (m)	Au Eq** (g/t)	Zn Eq** (g/t)	Au (g/t)	Ag (g/t)	Zn (%)	Cu (%)	Pb (%)	Type** *	Azimuth	Dip	UTM		Total Depth (m)
															Northing	Easting	
															GWM18-NK-01	149.40	
	347.60	348.10	0.50						0.8			DSS					
	348.10	348.90	0.80						0.5			DSS					
	364.90	366.00	1.10						0.8			DSS					
	370.60	371.20	0.60				22.3	1.6	0.7			DSS					
	390.40	392.20	1.80				12.9		0.5			DSS					
	403.90	404.40	0.50						0.5			DSS					
	405.60	406.30	0.80			0.3	33.7	0.2	0.7			DSS					
	423.00	445.00	22.00				12.8		0.5			DSS					
including	423.90	424.60	0.70				122.1		4.2			DSS					
including	432.80	433.40	0.60				53.5		2.4			DSS					
including	437.40	437.70	0.50				39.5		1.8			DSS					
including	439.30	440.00	0.70			0.9	20.7		0.9			DSS					
	472.00	472.70	0.70					0.6		0.3		DSS					
GWM18-NK-02	417.00	418.00	1.00				1.9	49.7		1.6		DSS	343	-75	5493148	662985	576.8
	432.75	433.25	0.50				0.3	46.1		1.2		DSS					
	441.75	442.30	0.60					50.7		1.0		DSS					
	545.30	545.85	0.60				0.2	145.0	6.7	2.1		DSS					
GWM18-NK-03	396.00	397.00	1.00				0.3	37.3		1.0		DSS	16	-73	5493148	662985	552
	420.20	427.30	7.10				0.1	25.1		1.2		DSS					
including	421.80	422.35	0.60				0.4	47.2		3.6		DSS					
including	423.55	424.15	0.60					80.8	1.2	4.1		DSS					
including	426.70	427.30	0.60				0.8	68.2		2.5		DSS					
GWM18-NK-05	No significant values											332	-51	5493516	661342	231	
GWM18-NK-06	No significant values											32	-61	5493516	661342	231	
GWM18-NK-10	Stopped before the targets due to lack of water											323	-45	5493071	664467	700	
GWM18-NK-12	272.00	273.00	1.00				2.5	128.7				DSS	323	-45	5493148	663663	600
	301.60	302.60	1.00				0.7					DSS					
	316.50	317.50	1.00					33.3	0.9	0.3		DSS					
	323.00	324.00	1.00				0.9	13.0	0.8		0.3	DSS					
	549.00	550.00	1.00				1.7					DSS					
GWM19-NK-04	329.30	329.90	0.60							0.3		DSS	350	-55	5492549	654906	633
	330.85	331.55	0.70							0.4		DSS					
	192.80	194.15	1.35						0.3			DSS					
	216.80	217.20	0.40						1.2			DSS					
	217.20	217.80	0.60						0.4			DSS					
	315.45	315.85	0.40					4.8		0.4		DSS					
	320.05	320.70	0.65					10.4		1.5		DSS					
	357.25	358.05	0.80					10.8		0.9		DSS					
	414.20	414.95	0.75					12.1				DSS					

Casa-Berardi Drill Hole Results																	
Hole #	From (m)	To (m)	Intercept (m)	TW (m)	Au Eq** (g/t)	Zn Eq** (g/t)	Au (g/t)	Ag (g/t)	Zn (%)	Cu (%)	Pb (%)	Type** *	Azimuth	Dip	UTM		Total Depth (m)
															Northing	Easting	
GWM-21CB-02	399.00	400.00	1.00				0.7						24	-58	5496085	654366	672
	460.95	461.50	0.55				0.8										
	465.00	466.00	1.00				0.4										
	468.50	469.00	0.50				0.3										
	469.50	469.50	0.50				0.5										
	524.00	525.00	1.00				0.2										
	438.00	439.00	1.00				0.3										
GWM-21CB-12	101.00	103.00	2.00				0.5						34	-63	5496085	654366	699
	111.00	112.00	1.00				1.65										
	557.00	557.50	0.50				0.55										

*Changed due so screen assay result

**Au (Eq g/t) and Zn (Eq %) represent the in-situ metal content expressed as Au and Zn equivalents.

Equivalents are not provided when the underlying Au and/or Zn metal content is below 25% of the intersect value.

Preliminary analysis indicates that no metal is dominant; however, Au and Zn are the largest contributors to the Estrades resource.

Equivalencies are calculated using the following metal prices (US\$) and exchange rate (US\$/C\$) provided by RPA:

Au \$1,450/oz, Ag \$21.00/oz, Zn \$1.15/lb, Cu \$3.50/lb, Pb \$1.00/lb, US\$0.80/C\$1.00.

***MSS = massive sulphide, SMS = semi-massive sulphide DSS = disseminated and stringer sulphides.

Holes were not drilled in sequential numerical order. If true width (TW) is not specified, the orientation of the zone is unknown at this time.